



Bee-flection Hive Observation Hive

- Optional to paint or stain outside of hive only
- Remove bottom and top part of hive from carton



- In the bottom, remove frames



- Insert wax in the frames by sliding the wax into the top of the frame



- Insert support pin into each side of the end bar, to support the wax.





- Install 5 Frames in the bottom



- Remove the feeder lid by unlatching top. Pull out frame and insert wax and support pins



- Reattach feeder lid





- In the wall that the Observation hive is being set up on, put a hole for a 1 inch tube



- Once the hole is inserted tube into the Observation hive. Plug the opposite end up with anything such as newspaper or paper towels
- Mix sugar water and put in jar. Use the feeder cap that is provided to close jar

To Install Bees

- Mist the bees in the cage with a spray bottle. All the bees need is a light misting to calm them down.
- Break 4 corners of the mason board on the cage of the bees with a hive tool, while holding your hand on the top of the cage.
- Holding the lid down with your thumbs, pick up the bees package, tap the package on the ground to cause the bees to fall to the bottom
- Remove lid and remove queen cage and feeder can. Place mason lid back on cage
- Set the feeder can on top of the package just to hold the lid down.
- Remove cork from candy end of queen cage
- Remove three frames from the bottom of the Observation hive
- Tap bees again down in their cage
- Remove lid
- Turn cage upside down and shake the bees into the Observation hive
- Install 2 of the three frames. Put the queen cage between 2 top bars (screen side up)
- Latch the top part on the take to the sight of installation. Put the tube through the wall. Leave the end stopped up.
- Once through wall go outside and unstop the end of the tube
- In 3 days go back in and check queen to see if she was released and add the fifth frame